Index to

EXPERIMENTAL MECHANICS

Volume 41, 2001

TITLE INDEX

Accelerometer Spiking Under Cryogenic Conditions—S. J. DiMaggio, Z. H. Duron and S. Rubin, 174-181 (June).

Accurate Integration of Surface Profile Data with Quantitative Error Analysis—N. Li, P. Cheng, M. A. Sutton, S. R. McNeill and Y. J. Chao, 77-83 (Mar.).

Acoustic Emission Monitoring of Carbon-fiber-reinforced-polymer Bridge Stay Cables in Large-scale Testing—P. Rizzo and F. Lanza di Scalea, 282-290 (Sept.).

Acoustoelastic Determination of Residual Stress with Laser Doppler Velocimetry—L. F. He and S. Kobayashi, 190-194 (June).

Advances in Scanning Electron Microscope Moiré—H. Chen and D. Liu, 165-173 (June).

Analysis of Strain Localization During Tensile Tests by Digital Image Correlation—B. Wattrisse, A. Chrysochoos, J.-M. Muracciole and M. Némoz-Gaillard, 29-39 (Mar.).

Brittle Fracture: Variation of Fracture Toughness with Constraint and Crack Curving Under Mode I Conditions—Y. J. Chao, S. Liu and B. J. Broviak, 232-241 (Sept.).

Buckling Investigations on a Nuclear Reactor Inner Vessel Model—M.R.S.C. Bose, G. Thomas, R. Palaninathan, S. P. Damodaran and P. Chellapandi, 144-150 (June).

Composite Specimen Bearing Failure Reduction in Iosipescu Shear Tests—B. W. Tew, E. M. Odom and J. D. Teel, 218-224 (Sept.).

Crack-opening Interferometry at Interfaces of Transparent Materials and Metals—J. W. Kysar, 52-57 (Mar.).

Development and Assessment of a Single-image Fringe Projection Method for Dynamic Applications—M. A. Sutton, W. Zhao, S. R. McNeill, H. W. Schreier and Y. J. Chao, 205-217 (Sept.).

Development of High-temperature Microsample Testing—M. Zupan, M. J. Hayden, C. J. Boehlert and K. J. Hemker, 242-247 (Sept.).

Effect of Plastic Zone on the Fatigue Crack Propagation Behavior Between Two Fatigue Cracks—S.-H. Song and B.-H. Choi, 225-231 (Sept.).

Electronic Speckle Pattern Interferometry Analysis of Tensile Tests of Semihard Copper Sheets—C. Vial-Edwards, I. Lira, A. Martinez and M. Münzenmayer, 58-62 (Mar.).

Embedded Optical Fiber Bragg Grating Sensor in a Nonuniform Strain Field: Measurements and Simulations—K. Peters, M. Studer, J. Botsis, A. Iocco, H. Limberger and R. Salathé, 19-28 (Mar.).

Errors in Crack Closure Measurements Caused by Flexure Test Fixture Support Effects—S. Johansson and M. E. Fitzpatrick, 47-51 (Mar.).

Experimental Analysis and Modeling of Biaxial Mechanical Behavior of Woven Composite Reinforcements—K. Buet-Gautier and P. Boisse, 260-269 (Sept.).

Experimental and Numerical Analysis of Vibrating Cracked Plates at Resonant Frequencies—C.-C. Ma and C.-H. Huang, 8-18 (Mar.).

Experimental Investigation of Dynamic Punch Tests on Isotropic and Composite Materials—C. Rubio-Gonzalez and J. J. Mason, 129-139 (June).

Experimental Investigation of Slosh Dynamics of Liquid-filled Containers—N. C. Pal, S. K. Bhattacharyya and P. K. Sinha, 63-69 (Mar.).

Experimental Study on Employing Flexural Wave Measurement to Characterize Delamination in Beams—S. I. Ishak, G. R. Liu, S. P. Lim and H. M. Shang, 157-164 (June).

Failure of Spot Welds under In-plane Static Loading—P. Wung, T. Walsh, A. Ourchane, W. Stewart and M. Jie, 100-106 (Mar.).

Fatigue Crack Shape Development of Plate-to-plate Welded Joints—S. T. Lie, S. P. Chiew, Z. Xiang and Z. Cen, 114-121 (Mar.).

Force and Shapes of Liquid Bridges Between Circular Pads—M. A. Verges, M. C. Larson and R. Bacou, 351-357 (Dec.).

A Force-based Failure Criterion for Spot Weld Design—P. Wung, 107-113 (Mar.).

Hybrid Experimental-numerical Concept of Residual Stress Analysis in Laser Weldments—D. Holstein, L. Salbut, M. Kujawinska and W. Jüptner, 343-350 (Dec.).

Hybrid Stress Analysis of Perforated Composites Using Strain Gages—T. H. Baek and R. E. Rowlands, 195-203 (June).

Hygric Characterization of Composites Using an Antisymmetric Cross-ply Specimen—C.-L. Tsai, S.-C. Wooh, S.-F. Hwang and Y. Du, 270-276 (Sept.).

Hygric Characterization of Woven Glass/Epoxy Composites—C.-L. Tsai and S.-C. Wooh, 70-76 (Mar.).

Investigation of Displacement Fields in an Abrasive Waterjet Drilling Process: Part 1. Experimental Measurements—Z. Guo and M. Ramulu, 375-387 (Dec.).

Investigation of Displacement Fields in an Abrasive Waterjet Drilling Process: Part 2. Numerical Analysis—Z. Guo and M. Ramulu, 388-402 (Dec.).

Measurement of Coatings' Elastic Properties by Mechanical Methods: Part 1. Experimental Errors—M. Beghini, L. Bertini and F. Frendo, 293-304 (Dec.).

Measurement of Coatings' Elastic Properties by Mechanical Methods: Part 2. Application to Thermal Barrier Coatings—M. Beghini, G. Benamati, L. Bertini and F. Frendo, 305-311 (Dec.).

Measurement of Steering Gear Impedance—M. S. Qatu, D. R. Llewellyn and W. G. Spadafora, 151-156 (June).

A Method for Measuring the Creep Behavior of Pressurized Polymer Tubing—C. Wu, S. C. Mantell and J. H. Davidson, 368-374 (Dec.).

A New Moiré Interferometer for Measuring In-plane Displacement—S. T. Lin, 140-143 (June).

Nonlinear Behavior of Composite Sandwich Beams in Three-point Bending—E. E. Gdoutos, I. M. Daniel, K.-A. Wang and J. L. Abot, 182-189 (June).

Photoelastic Experimental Hybrid Method for Fracture Mechanics of Anisotropic Materials—J.-S. Hawong, D.-C. Shin and H.-J. Lee, 92-99 (Mar.).

Photoviscoelastic Stress Analysis of a Plate with a Central Hole—Y.-H. Zhao and J. Huang, 312-318 (Dec.).

Pressure Effects and Fracture of a Rubbery Particulate Composite—T. C. Miller and C. T. Liu, 254-259 (Sept.).

Residual Stress Determination Using Blind-hole Drilling and Digital Speckle Pattern Interferometry with Automated Data Processing—F. V. Díaz, G. H. Kaufmann and O. Möller, 319-323 (Dec.).

Spectrotemporal Analysis of Guided-wave Pulse-echo Signals: Part 1. Dispersive Systems—S.-C. Wooh and K. Veroy, 324-331 (Dec.).

Spectrotemporal Analysis of Guided-wave Pulse-echo Signals: Part 2. Numerical and Experimental Investigations—S.-C. Wooh and K. Veroy, 332-342 (Dec.).

A Split Hopkinson Pressure Bar Technique to Determine Compressive Stress-strain Data for Rock Materials—D. J. Frew, M. J. Forrestal and W. Chen, 40-46 (Mar.).

Strain Gage Method for Determining Stress Intensities of Sharp-notched Strips—T. Kondo, M. Kobayashi and H. Sekine, 1-7 (Mar.).

Stress Evaluation by Pulse-echo Ultrasonic Longitudinal Wave—D. Vangi, 277-281 (Sept.).

Stress Separation of Thermoelastically Measured Isopachics—B. J. Rauch and R. E. Rowlands, 358-367 (Dec.).
A Technique for Rapid Two-stage Dynamic Tensile Loading of Polymers—V.P.W. Shim, J. Yuan and S.-H. Lee, 122-127 (Mar.).
Three-dimensional Crack Tip Deformation Measurement Using Combined Moiré-Sagnac Interferometry—B.S.-J. Kang and S. M. Anderson, 84-91 (Mar.).
Torsion Measurement Using Fiber Bragg Grating Sensors—X. G. Tian and X. M. Tao, 248-253 (Sept.).

AUTHOR INDEX

Abot, J. L.—Nonlinear Behavior of Composite Sandwich Beams in Three-point Bending, 182-189 (June).
Anderson, S. M.—Three-dimensional Crack Tip Deformation Measurement Using Combined Moiré-Sagnac Interferometry, 84-91 (Mar.).
Bacou, R.—Force and Shapes of Liquid Bridges Between Circular Pads, 351-357 (Dec.).
Baek, T. H.—Hybrid Stress Analysis of Perforated Composites Using Strain Gages, 195-203 (June).
Beghini, M.—Measurement of Coatings' Elastic Properties by Mechanical Methods: Part 1. Experimental Errors, 293-394 (Dec.).
Beghini, M.—Measurement of Coatings' Elastic Properties by Mechanical Methods: Part 2. Application to Thermal Barrier Coatings, 305-311 (Dec.).
Benamati, G.—Measurement of Coatings' Elastic Properties by Mechanical Methods: Part 2. Application to Thermal Barrier Coatings, 305-311 (Dec.).
Bertini, L.—Measurement of Coatings' Elastic Properties by Mechanical Methods: Part 1. Experimental Errors, 293-304 (Dec.).
Bertini, L.—Measurement of Coatings' Elastic Properties by Mechanical Methods: Part 2. Application to Thermal Barrier Coatings, 305-311 (Dec.).
Bhattacharyya, S. K.—Experimental Investigation of Slosh Dynamics of Liquid-filled Containers, 63-69 (Mar.).
Boehlert, C. J.—Development of High-temperature Microsample Testing, 242-247 (Sept.).
Boisse, P.—Experimental Analysis and Modeling of Biaxial Mechanical Behavior of Woven Composite Reinforcements, 260-269 (Sept.).
Bose, M.R.S.C.—Buckling Investigations on a Nuclear Reactor Inner Vessel Model, 144-150 (June).
Botsis, J.—Embedded Optical Fiber Bragg Grating Sensor in a Nonuniform Strain Field: Measurements and Simulations, 19-28 (Mar.).
Broviak, B. J.—Brittle Fracture: Variation of Fracture Toughness with Constraint and Crack Curving Under Mode I Conditions, 232-241 (Sept.).
Buet-Gautier, K.—Experimental Analysis and Modeling of Biaxial Mechanical Behavior of Woven Composite Reinforcements, 260-269 (Sept.).
Cen, Z.—Fatigue Crack Shape Development of Plate-to-plate Welded Joints, 114-121 (Mar.).
Chao, Y. J.—Accurate Integration of Surface Profile Data with Quantitative Error Analysis, 77-83 (Mar.).
Chao, Y. J.—Brittle Fracture: Variation of Fracture Toughness with Constraint and Crack Curving Under Mode I Conditions, 232-241 (Sept.).
Chao, Y. J.—Development and Assessment of a Single-image Fringe Projection Method for Dynamic Applications, 205-217 (Sept.).
Chellapandi, P.—Buckling Investigations on a Nuclear Reactor Inner Vessel Model, 144-150 (June).
Chen, H.—Advances in Scanning Electron Microscope Moiré, 165-173 (June).
Chen, W.—A Split Hopkinson Pressure Bar Technique to Determine Compressive Stress-strain Data for Rock Materials, 40-46 (Mar.).
Cheng, P.—Accurate Integration of Surface Profile Data with Quantitative Error Analysis, 77-83 (Mar.).
Chiew, S. P.—Fatigue Crack Shape Development of Plate-to-plate Welded Joints, 114-121 (Mar.).
Choi, B.-H.—Effect of Plastic Zone on the Fatigue Crack Propagation Behavior Between Two Fatigue Cracks, 225-231 (Sept.).
Chrysochoos, A.—Analysis of Strain Localization During Tensile Tests by Digital Image Correlation, 29-39 (Mar.).
Damodaran, S. P.—Buckling Investigations on a Nuclear Reactor Inner Vessel Model, 144-150 (June).
Daniel, I. M.—Nonlinear Behavior of Composite Sandwich Beams in Three-point Bending, 182-189 (June).
Davidson, J. H.—A Method for Measuring the Creep Behavior of Pressurized Polymer Tubing, 368-374 (Dec.).
Díaz, F. V.—Residual Stress Determination Using Blind-hole Drilling and Digital Speckle Pattern Interferometry with Automated Data Processing, 319-324 (Dec.).
DiMaggio, S. J.—Accelerometer Spiking Under Cryogenic Conditions, 174-181 (June).
Du, Y.—Hygric Characterization of Composites Using an Antisymmetric Cross-ply Specimen, 270-276 (Sept.).
Duron, Z. H.—Accelerometer Spiking Under Cryogenic Conditions, 174-181 (June).
Fitzpatrick, M. E.—Errors in Crack Closure Measurements Caused by Flexure Test Fixture Support Effects, 47-51 (Mar.).
Forrestal, M. J.—A Split Hopkinson Pressure Bar Technique to Determine Compressive Stress-strain Data for Rock Materials, 40-46 (Mar.).
Frendo, F.—Measurement of Coatings' Elastic Properties by Mechanical Methods: Part 1. Experimental Errors, 293-304 (Dec.).
Frendo, F.—Measurement of Coatings' Elastic Properties by Mechanical Methods: Part 2. Application to Thermal Barrier Coatings, 305-311 (Dec.).
Frew, D. J.—A Split Hopkinson Pressure Bar Technique to Determine Compressive Stress-strain Data for Rock Materials, 40-46 (Mar.).
Gdoutos, E. E.—Nonlinear Behavior of Composite Sandwich Beams in Three-point Bending, 182-189 (June).
Guo, Z.—Investigation of Displacement Fields in an Abrasive Waterjet Drilling Process: Part 1. Experimental Measurements, 375-387 (Dec.).
Guo, Z.—Investigation of Displacement Fields in an Abrasive Waterjet Drilling Process: Part 2. Numerical Analysis, 388-402 (Dec.).
Hawong, J.-S.—Photoelastic Experimental Hybrid Method for Fracture Mechanics of Anisotropic Materials, 92-99 (Mar.).
Hayden, M. J.—Development of High-temperature Microsample Testing, 242-247 (Sept.).
He, L. F.—Acoustoelastic Determination of Residual Stress with Laser Doppler Velocimetry, 190-194 (June).
Hemker, K. J.—Development of High-temperature Microsample Testing, 242-247 (Sept.).
Holstein, D.—Hybrid Experimental-numerical Concept of Residual Stress Analysis in Laser Weldments, 343-350 (Dec.).
Huang, C.-H.—Experimental and Numerical Analysis of Vibrating Cracked Plates at Resonant Frequencies, 8-18 (Mar.).
Huang, J.—Photoviscoelastic Stress Analysis of a Plate with a Central Hole, 312-318 (Dec.).
Hwang, S.-F.—Hygric Characterization of Composites Using an Antisymmetric Cross-ply Specimen, 270-276 (Sept.).
Iocco, A.—Embedded Optical Fiber Bragg Grating Sensor in a Nonuniform Strain Field: Measurements and Simulations, 19-28 (Mar.).
Ishak, S. I.—Experimental Study on Employing Flexural Wave Measurement to Characterize Delamination in Beams, 157-164 (June).
Jie, M.—Failure of Spot Welds under In-plane Static Loading, 100-106 (Mar.).

Johansson, S.—Errors in Crack Closure Measurements Caused by Flexure Test Fixture Support Effects, 47-51 (Mar.).
Jüptner, W.—Hybrid Experimental-numerical Concept of Residual Stress Analysis in Laser Weldments, 343-350 (Dec.).
Kang, B.S.-J.—Three-dimensional Crack Tip Deformation Measurement Using Combined Moiré-Sagnac Interferometry, 84-91 (Mar.).
Kaufmann, G. H.—Residual Stress Determination Using Blind-hole Drilling and Digital Speckle Pattern Interferometry with Automated Data Processing, 319-323 (Dec.).
Kobayashi, M.—Strain Gage Method for Determining Stress Intensities of Sharp-notched Strips, 1-7 (Mar.).
Kobayashi, S.—Acoustoelastic Determination of Residual Stress with Laser Doppler Velocimetry, 190-194 (June).
Kondo, T.—Strain Gage Method for Determining Stress Intensities of Sharp-notched Strips, 1-7 (Mar.).
Kujawinska, M.—Hybrid Experimental-numerical Concept of Residual Stress Analysis in Laser Weldments, 343-350 (Dec.)
Kysar, J. W.—Crack-opening Interferometry at Interfaces of Transparent Materials and Metals, 52-57 (Mar.).
Lanza di Scalea, F.—Acoustic Emission Monitoring of Carbon-fiber-reinforced-polymer Bridge Stay Cables in Large-scale Testing, 282-290 (Sept.).
Larson, M. C.—Force and Shapes of Liquid Bridges Between Circular Pads, 351-357 (Dec.).
Lee, H.-J.—Photoelastic Experimental Hybrid Method for Fracture Mechanics of Anisotropic Materials, 92-99 (Mar.).
Lee, S.-H.—A Technique for Rapid Two-stage Dynamic Tensile Loading of Polymers, 122-127 (Mar.).
Li, N.—Accurate Integration of Surface Profile Data with Quantitative Error Analysis, 77-83 (Mar.).
Lie, S. T.—Fatigue Crack Shape Development of Plate-to-plate Welded Joints, 114-121 (Mar.).
Lim, S. P.—Experimental Study on Employing Flexural Wave Measurement to Characterize Delamination in Beams, 157-164 (June).
Limberger, H.—Embedded Optical Fiber Bragg Grating Sensor in a Nonuniform Strain Field: Measurements and Simulations, 19-28 (Mar.).
Lin, S. T.—A New Moiré Interferometer for Measuring In-plane Displacement, 140-143 (June).
Lira, I.—Electronic Speckle Pattern Interferometry Analysis of Tensile Tests of Semihard Copper Sheets, 58-62 (Mar.).
Liu, C. T.—Pressure Effects and Fracture of a Rubbery Particulate Composite, 254-259 (Sept.).
Liu, D.—Advances in Scanning Electron Microscope Moiré, 165-173 (June).
Liu, G. R.—Experimental Study on Employing Flexural Wave Measurement to Characterize Delamination in Beams, 157-164 (June).
Liu, S.—Brittle Fracture: Variation of Fracture Toughness with Constraint and Crack Curving Under Mode I Conditions, 232-241 (Sept.).
Llewellyn, D. R.—Measurement of Steering Gear Impedance, 151-156 (June).
Ma, C.-C.—Experimental and Numerical Analysis of Vibrating Cracked Plates at Resonant Frequencies, 8-18 (Mar.).
Mantell, S. C.—A Method for Measuring the Creep Behavior of Pressurized Polymer Tubing, 368-374 (Dec.).
Martinez, A.—Electronic Speckle Pattern Interferometry Analysis of Tensile Tests of Semihard Copper Sheets, 58-62 (Mar.).
Mason, J. J.—Experimental Investigation of Dynamic Punch Tests on Isotropic and Composite Materials, 129-139 (June).
McNeill, S. R.—Accurate Integration of Surface Profile Data with Quantitative Error Analysis, 77-83 (Mar.).
McNeill, S. R.—Development and Assessment of a Single-image Fringe Projection Method for Dynamic Applications, 205-217 (Sept.).
Miller, T. C.—Pressure Effects and Fracture of a Rubbery Particulate Composite, 254-259 (Sept.).
Möller, O.—Residual Stress Determination Using Blind-hole Drilling and Digital Speckle Pattern Interferometry with Automated Data Processing, 319-323 (Dec.).
Münzemayer, M.—Electronic Speckle Pattern Interferometry Analysis of Tensile Tests of Semihard Copper Sheets, 58-62 (Mar.).
Muracciole, J.-M.—Analysis of Strain Localization During Tensile Tests by Digital Image Correlation, 29-39 (Mar.).
Némoz-Gaillard, M.—Analysis of Strain Localization During Tensile Tests by Digital Image Correlation, 29-39 (Mar.).
Odom, E. M.—Composite Specimen Bearing Failure Reduction in Iosipescu Shear Tests, 218-224 (Sept.).
Ourchane, A.—Failure of Spot Welds under In-plane Static Loading, 100-106 (Mar.).
Pal, N. C.—Experimental Investigation of Slosh Dynamics of Liquid-filled Containers, 63-69 (Mar.).
Palaninathan, R.—Buckling Investigations on a Nuclear Reactor Inner Vessel Model, 144-150 (June).
Peters, K.—Embedded Optical Fiber Bragg Grating Sensor in a Nonuniform Strain Field: Measurements and Simulations, 19-28 (Mar.).
Qatu, M. S.—Measurement of Steering Gear Impedance, 151-156 (June).
Ramulu, M.—Investigation of Displacement Fields in an Abrasive Waterjet Drilling Process: Part 1. Experimental Measurements, 375-387 (Dec.).
Ramulu, M.—Investigation of Displacement Fields in an Abrasive Waterjet Drilling Process: Part 2. Numerical Analysis, 388-402 (Dec.).
Rauch, B. J.—Stress Separation of Thermoelastically Measured Isopachics, 358-367 (Dec.).
Rizzo, P.—Acoustic Emission Monitoring of Carbon-fiber-reinforced-polymer Bridge Stay Cables in Large-scale Testing, 282-290 (Sept.).
Rowlands, R. E.—Hybrid Stress Analysis of Perforated Composites Using Strain Gages, 195-203 (June).
Rowlands, R. E.—Stress Separation of Thermoelastically Measured Isopachics, 358-367 (Dec.).
Rubin, S.—Accelerometer Spiking Under Cryogenic Conditions, 174-181 (June).
Rubio-Gonzalez, C.—Experimental Investigation of Dynamic Punch Tests on Isotropic and Composite Materials, 129-139 (June).
Salathé, R.—Embedded Optical Fiber Bragg Grating Sensor in a Nonuniform Strain Field: Measurements and Simulations, 19-28 (Mar.).
Salbut, L.—Hybrid Experimental-numerical Concept of Residual Stress Analysis in Laser Weldments, 343-350 (Dec.).
Schreier, H. W.—Development and Assessment of a Single-image Fringe Projection Method for Dynamic Applications, 205-217 (Sept.).
Sekine, H.—Strain Gage Method for Determining Stress Intensities of Sharp-notched Strips, 1-7 (Mar.).
Shang, H. M.—Experimental Study on Employing Flexural Wave Measurement to Characterize Delamination in Beams, 157-164 (June).
Shim, V.P.W.—A Technique for Rapid Two-stage Dynamic Tensile Loading of Polymers, 122-127 (Mar.).
Shin, D.-C.—Photoelastic Experimental Hybrid Method for Fracture Mechanics of Anisotropic Materials, 92-99 (Mar.).
Sinha, P. K.—Experimental Investigation of Slosh Dynamics of Liquid-filled Containers, 63-69 (Mar.).
Song, S.-H.—Effect of Plastic Zone on the Fatigue Crack Propagation Behavior Between Two Fatigue Cracks, 225-231 (Sept.).
Spadafora, W. G.—Measurement of Steering Gear Impedance, 151-156 (June).
Stewart, W.—Failure of Spot Welds under In-plane Static Loading, 100-106 (Mar.).
Studer, M.—Embedded Optical Fiber Bragg Grating Sensor in a Nonuniform Strain Field: Measurements and Simulations, 19-28 (Mar.).
Sutton, M. A.—Accurate Integration of Surface Profile Data with Quantitative Error Analysis, 77-83 (Mar.).
Sutton, M. A.—Development and Assessment of a Single-image Fringe Projection Method for Dynamic Applications, 205-217 (Sept.).
Tao, X. M.—Torsion Measurement Using Fiber Bragg Grating Sensors, 248-253 (Sept.).
Teel, J. D.—Composite Specimen Bearing Failure Reduction in Iosipescu Shear Tests, 218-224 (Sept.).
Tew, B. W.—Composite Specimen Bearing Failure Reduction in Iosipescu Shear Tests, 218-224 (Sept.).
Thomas, G.—Buckling Investigations on a Nuclear Reactor Inner Vessel Model, 144-150 (June).

Tian, X. G.—Torsion Measurement Using Fiber Bragg Grating Sensors, 248-253 (Sept.).
Tsai, C.-L.—Hygric Characterization of Composites Using an Antisymmetric Cross-ply Specimen, 270-276 (Sept.).
Tsai, C.-L.—Hygric Characterization of Woven Glass/Epoxy Composites, 70-76 (Mar.).
Vangi, D.—Stress Evaluation by Pulse-echo Ultrasonic Longitudinal Wave, 277-281 (Sept.).
Verges, M. A.—Force and Shapes of Liquid Bridges Between Circular Pads, 351-357 (Dec.).
Veroy, K.—Spectrotemporal Analysis of Guided-wave Pulse-echo Signals: Part 1. Dispersive Systems, 324-331 (Dec.).
Veroy, K.—Spectrotemporal Analysis of Guided-wave Pulse-echo Signals: Part 2. Numerical and Experimental Investigations, 332-342 (Dec.).
Vial-Edwards, C.—Electronic Speckle Pattern Interferometry Analysis of Tensile Tests of Semihard Copper Sheets, 58-62 (Mar.).
Walsh, T.—Failure of Spot Welds under In-plane Static Loading, 100-106 (Mar.).
Wang, K.-A.—Nonlinear Behavior of Composite Sandwich Beams in Three-point Bending, 182-189 (June).
Wattrisse, B.—Analysis of Strain Localization During Tensile Tests by Digital Image Correlation, 29-39 (Mar.).
Wooh, S.-C.—Hygric Characterization of Composites Using an Antisymmetric Cross-ply Specimen, 270-276 (Sept.).
Wooh, S.-C.—Hygric Characterization of Woven Glass/Epoxy Composites, 70-76 (Mar.).
Wooh, S.-C.—Spectrotemporal Analysis of Guided-wave Pulse-echo Signals: Part 1. Dispersive Systems, 324-331 (Dec.).
Wooh, S.-C.—Spectrotemporal Analysis of Guided-wave Pulse-echo Signals: Part 2. Numerical and Experimental Investigations, 332-342 (Dec.).
Wu, C.—A Method for Measuring the Creep Behavior of Pressurized Polymer Tubing, 368-374 (Dec.).
Wung, P.—Failure of Spot Welds under In-plane Static Loading, 100-106 (Mar.).
Wung, P.—A Force-based Failure Criterion for Spot Weld Design, 107-113 (Mar.).
Xiang, Z.—Fatigue Crack Shape Development of Plate-to-plate Welded Joints, 114-121 (Mar.).
Yuan, J.—A Technique for Rapid Two-stage Dynamic Tensile Loading of Polymers, 122-127 (Mar.).
Zhao, W.—Development and Assessment of a Single-image Fringe Projection Method for Dynamic Applications, 205-217 (Sept.).
Zhao, Y.-H.—Photoviscoelastic Stress Analysis of a Plate with a Central Hole, 312-318 (Dec.).
Zupan, M.—Development of High-temperature Microsample Testing, 242-247 (Sept.).